

"The Right Science"

ATMOSPHERE MARINE WASH

ATMOSPHERE MARINE WASH is a biodegradable all surface heavy duty cleaner, sanitiser, odour eliminator, designed specifically for the marine industry.

Formulated to effectively remove grease, grime, oils and salt spray in and on all marine surfaces while eliminating foul odours and bacteria within the bilge, holding area, toilets and other areas where cleaning, sanitation and odour control is imperative.

Perfect for the removal and prevention of Mould, Mildew and Algae.

EXTERIOR



Effectively removes Salt Spray & General Soiling.

BILGE



Eliminates Odour & Bacteria, Breaks Down Grease and Oil

INTERIOR



Eliminates Odor, Cleans Glass, Canvas, Vinyl, Aluminium, Antibacterial.

WORLD-WISE CERTIFIED

The earths ecological balance is important to us, and our caring is reflected in the products we produce.

This is supported by all our products approved to carry the WORLD-WISE LOGO on our labels.

The only Australasian company approved to do so.

- Have Only Zeros or Ones on HMIS® III Numbers for Health, Flammability, Physical Hazard.
- Must Contain No Volatile Organic Compounds (VOCs)
- Must Contain No Hazardous Components
- Must Contain No Nonylphenol Ethoxylates (NPEs)
- Must Contain No Ozone Depleting Substances (ODS)
- Must Contain No SARA Section 313 Reportable Ingredients
- Must Contain No Phosphates
- Must Contain No Heavy Metals
- Must Contain No Chlorine
- Must Contain No Phthalates (PVC)
- Must Be Packaged in Environmentally Responsible Packaging





Based in Sydney Australia & Chicago USA, ATMOSPHERE has undertaken extensive product research and successful field trials throughout Australia, New Zealand, Thailand and the USA with manufacturing & distribution in Australia (Sydney NSW, Gold Coast QLD) New Zealand (Auckland) & the USA (Chicago Illinois)

APPLICATIONS FOR MARINE WASH

500mL SPRAY BOTTLE: Spray & Wipe Solution

- > Apply MW directly into spray bottle at a 1 40 dilution
- ➤ Allow a distance of 1 foot from sprayer to designated surface.
- > Spray directly onto the surface (1 4 pumps, depending on the amount of soiling)
- > Allow to rest for no less than 90 seconds for heavy soiling & improved cleanliness.
- ➤ Wipe off with a clean cloth.

GLASS & STAINLESS STEEL

If streaking is occurring, dilute MW a further 1 – 20 with clean water, and continue with the above directions.

MOP & BUCKET

Add 200mL (1 cup) of MW into a standard size bucket of warm water.

- > Apply mop to the designated surface liberally
- > Allow to dry

PRESSURE WASHER

Add MW directly into a foam applicator at a 2.5 - 5% dilution

- > Apply MW activated foam liberally over the designated surfaces
- ➤ Allow the foam to settle on the surface to breakdown contamination (Blood-Fats-Oils etc.) and heavy soiling for no less than 90 seconds before rinsing
- ➤ Wash down thoroughly with hot (100 120 o C) potable (clean) water
- ➤ For heavy contamination & soiling, allow ATMOSPHERE to rest on the offending surface a little longer until the desired result is achieved.

ODOUR CONTROL

Dilute MW 1 – 100 with clean water into 500mL Spray Bottle and spray into / onto the offending area.

Perfect for use in Bilges, Toilets and other areas where foul and nasty odours are a concern.

ATMOSPHERE GLOBAL PTYLTD

Ph +61 423 703 903

Em info@atmosphere.global Wb www.atmosphere.global

